

## Stand-Alone Scrambler TSC-B



### Features

- DVB Common Scrambling Algorithm.
- Support Simulcrypt and various leading CAS.
- SPTS / MPTS input.
- Scramble chosen programs or Transport Streams.
- Scramble any combination of Video/Audio, data streams.
- 1~54Mbps input, bit rate auto adaptation.
- Output bit rate tunable.
- PCR restamping.
- Remote control via RJ45.
- 19", 1RU.

Input	Unit	Specifications
Interface Type	-	Asynchronous Serial Interface (ASI)
Connector Type	-	BNC, 75Ω
Number of Ports	-	2
Packet Format	Byte	188 / 204 auto
Bit Rate	Mbps	1 ~ 54
Syntax	-	SPTS or MPTS
<b>Output</b>		
Interface Type	-	Asynchronous Serial Interface (ASI)
Number of Ports	-	2
Connector	-	BNC, 75Ω
Packet Format	Byte	188 / 204 Auto detection
Bit Rate	Mbps	Max. 54Mbps (tunable)
Syntax	-	SPTS or MPTS
<b>Remote Control</b>		
Number of Connectors	-	1
Connector Type	-	RJ-45, 10/100Base-T
<b>Others</b>		
Power Supply	V	AC 220V, 50Hz